



Stirrers with PTFE blade and GL thread connection

Stirrers with PTFE blade and
GL thread connection

Made of precision calibrated glass tube,
ground and polished bearing surface,
shaft dia.: 10 mm, thread connection: GL 10,
with snap-fastener for replacement of PTFE blades,
blade: PTFE (punched),
shaft: made of DURAN® tubing

PTFE blades

With bore (6 mm) for snap-fastener,
material: PTFE, punched

For flask (ml)	For joint (NS)	Length (mm)	Blade L x H X dia. (mm)	Bores no./dia. (mm)	Pack (qty.)	Cat. No.
100	29/32	270	55 x 17 x 3	2/5	1	6 3150 31
250	29/32	280	55 x 17 x 3	2/5	1	6 3150 33
500	29/32	300	80 x 20 x 3	4/5	1	6 3150 35
1000	45/40	370	80 x 20 x 3	6/6	1	6 3150 37
2000	45/40	425	98 x 20 x 3	6/7	1	6 3150 38
4000	45/40	480	105 x 25 x 4	6/7	1	6 3150 41
6000	45/40	515	115 x 25 x 4	6/7	1	6 3150 45

For flask (ml)	Dimensions L x H X dia. (mm)	Bores no./dia. (mm)	Pack (qty.)	Cat. No.
100/250	55 x 17 x 3	2/5	1	6 3152 01
500	80 x 20 x 3	4/5	1	6 3152 05
1000	80 x 20 x 3	6/6	1	6 3152 07
2000	98 x 20 x 3	6/7	1	6 3152 08

4000	105 x 25 x 4	6/7	1	6 3152 11
6000	115 x 25 x 4	6/7	1	6 3152 15

Generated on 2026-05-19